

# LOCHINVAR TO PERFECT FIT

| Lochinvar                |         |     |         |         | Perfect Fit |         |     |         |           |
|--------------------------|---------|-----|---------|---------|-------------|---------|-----|---------|-----------|
| Model                    | Btu/h   | Gal | Dia.    | Height  | Model       | Btu/h   | Gal | Dia.    | Height    |
| <b>CNR Series</b>        |         |     |         |         |             |         |     |         |           |
| CNR080-075               | 80,000  | 75  | 26"     | 63-3/4" | T75-75N-2   | 75,100  | 75  | 26-1/4" | 64"       |
| CNR090-100               | 88,000  | 100 | 28-1/4" | 68-5/8" | T100-80     | 80,000  | 100 | 28-1/4" | 69-5/8"   |
| CNR145-035-DF9           | 145,000 | 35  | 28-1/4" | 50-5/8" | T37-200     | 199,900 | 35  | 26-1/4" | 49-1/4"   |
| CNR125-075-DF9           | 125,000 | 75  | 28-1/4" | 72-1/8" | T75-125     | 125,000 | 75  | 26-1/4" | 65-1/2"   |
| CNR160-075-DF9           | 160,000 | 75  | 28-1/4" | 72-1/8" | T82-156     | 156,000 | 82  | 26-1/4" | 68-13/16" |
| CNR180-080-DF9           | 180,000 | 80  | 28-1/4" | 71-7/8" | T76-180     | 180,000 | 76  | 26-1/4" | 68-13/16" |
| CNR200-080-DF9           | 199,999 | 80  | 28-1/4" | 71-7/8" | T76-200     | 199,900 | 76  | 26-1/4" | 68-13/16" |
| CNR200-100-DF9           | 199,999 | 98  | 28-1/4" | 83"     | T91-200     | 199,900 | 91  | 26-1/4" | 76-5/16"  |
| <b>CNA (ASME) Series</b> |         |     |         |         |             |         |     |         |           |
| CNA251-100-DF9           | 250,000 | 98  | 28-1/4" | 83"     | T100-250(A) | 250,000 | 100 | 30-1/4" | 73-1/4"   |
| CNA301-075-DF9           | 300,000 | 75  | 28-1/4" | 74"     | T72-300(A)  | 300,000 | 72  | 26-1/4" | 71"       |
| CNA371-065-DF9           | 370,000 | 65  | 28-1/4" | 74"     | T65-360(A)  | 360,000 | 65  | 26-1/4" | 70-11/16" |
| CNA401-080-DF9           | 399,999 | 80  | 30-1/4" | 77-1/4" | T85-400(A)  | 399,900 | 85  | 26-1/4" | 78-13/16" |

| Model  | kW     | Gal | Model   | kW     | Gal |
|--|--------|-----|---------|--------|-----|
| <b>Electric – Light Duty and Point-of-Use Products</b> |        |     |         |        |     |
| ETX/ETW030KK   | 12 Max | 30  | TELD30  | 12 Max | 30  |
| ESX/ESW030KK   | 12 Max | 30  | TELDS30 | 12 Max | 30  |
| ETX/ETW040KK   | 12 Max | 40  | TELD40  | 12 Max | 40  |
| ESX/ESW040KK   | 12 Max | 40  | TELDS40 | 12 Max | 40  |
| ETX/ETW052KK   | 12 Max | 50  | TELD52  | 12 Max | 50  |
| ESX/ESW050KK   | 12 Max | 50  | TELDS52 | 12 Max | 50  |
| ETX/ETW066KK   | 12 Max | 65  | TELD66  | 12 Max | 65  |
| ETX/ETW082KK   | 12 Max | 80  | TELD80  | 12 Max | 80  |
| ETX/ETW120KK   | 12 Max | 120 | TELD120 | 12 Max | 120 |

NOTE: "ETX/ESX" refers to 480 volt, 3 phase products. "ETW/ESW" refers to 277 volt, 1 phase products.  
 NOTE: "TELD/TELDS" models are available in 208, 240, 277 or 480 volt (1 or 3 phase) configurations.

|                                       |         |     |        |         |     |
|---------------------------------------|---------|-----|--------|---------|-----|
| <b>Electric – Heavy Duty Products</b> |         |     |        |         |     |
| HS*(kW)-052                           | 9 to 36 | 52  | TES50  | 6 to 54 | 50  |
| HS*(kW)-082                           | 9 to 54 | 82  | TES85  | 6 to 54 | 85  |
| HS*(kW)-120(A)                        | 9 to 54 | 118 | TES120 | 6 to 54 | 120 |
| HC*(kW)-052                           | 9 to 36 | 52  | TE50   | 6 to 54 | 50  |
| HC*(kW)-082                           | 9 to 54 | 82  | TE85   | 6 to 54 | 85  |
| HC*(kW)-120(A)                        | 9 to 54 | 118 | TE120  | 6 to 54 | 120 |

|   |    |     |        |    |     |
|---|----|-----|--------|----|-----|
| <b>Storage Tank Systems (**Unfired Storage Vessels)</b> |    |     |        |    |     |
| RJS080  | ** | 78  | ST80   | ** | 80  |
| RJS085  | ** | 85  | ST80   | ** | 80  |
| RJS120  | ** | 119 | ST120  | ** | 115 |
| RJA120  | ** | 119 | ST120A | ** | 115 |
| RJA200  | ** | 200 | ST175A | ** | 175 |

|  |         |   |      |         |    |
|--|---------|---|------|---------|----|
| <b>Electric – Instantaneous/Booster Products</b> |         |   |      |         |    |
| SB*-(kW)   | 6 to 58 | 5 | TE10 | 6 to 54 | 10 |

NOTE: \* Refers to voltage/phase:

A – 240 Volt, 1 Phase      B – 240 Volt, 3 Phase  
 J – 208 Volt, 1 Phase      K – 208 Volt, 3 Phase  
 P – 240 Volt, 1/3 Phase      T – 208 Volt, 1/3 Phase  
 W – 277 Volt, 1 Phase      X – 480 Volt, 3 Phase  
 R – Special - Must Specify