

**BRADFORD WHITE TO PERFECT FIT**

Bradford White					Perfect Fit				
Model	Btu/h	Gal	Dia.	Height	Model	Btu/h	Gal	Dia.	Height
<b>T&amp;S Series</b>									
75T-80	80,000	75	26"	63-3/4"	T75-75N-2	75,100	75	26-1/4"	64"
100T-88	88,000	100	28-1/4"	68-5/8"	T100-80	80,000	100	28-1/4"	69-5/8"
D-75T-125-3N	125,000	75	28-1/4"	72-1/8"	T75-125	125,000	75	26-1/4"	65-1/2"
D-38T-155	155,000	38	28-1/4"	51"	T37-200	199,900	35	26-1/4"	49-1/4"
D-75T-160-3N	160,000	75	28-1/4"	72-1/8"	T82-156	156,000	82	26-1/4"	68-13/16"
D-80T-180-3N	180,000	80	28-1/4"	71-7/8"	T76-180	180,000	76	26-1/4"	68-13/16"
D-80T-199-3N	199,999	80	28-1/4"	71-7/8"	T76-200	199,900	76	26-1/4"	68-13/16"
D-100T-199-3N	199,999	98	28-1/4"	83"	T91-200	199,900	91	26-1/4"	76-5/16"
D-100S-199-3N	199,999	100	30-1/4"	74-1/4"	T100-200(A)	199,990	100	30-1/4"	73-1/16"
D-80T-250-3N(A)	250,000	80	28-1/4"	71-7/8"	T72-250(A)	250,000	72	26-1/4"	71-1/16"
D-100S-250-3N(A)	250,000	100	30-1/4"	74-1/4"	T100-250(A)	250,000	100	30-1/4"	73-1/4"
D-100T-250-3N(A)	250,000	98	28-1/4"	83"	T100-250(A)	250,000	100	30-1/4"	73-1/4"
D-100S-270-3N(A)	270,000	100	30-1/4"	74-1/4"	T100-270(A)	270,000	100	30-1/4"	73-7/8"
D-75T-300-3N(A)	300,000	75	28-1/4"	74"	T72-300(A)	300,000	72	26-1/4"	71"
D-65T-370-3N(A)	370,000	65	28-1/4"	74"	T65-360(A)	360,000	65	26-1/4"	70-11/16"
D-65T-399-3N(A)	399,999	65	28-1/4"	74"	T65-400(A)	399,900	65	26-1/4"	70-11/16"
D-80S-399-3N(A)	399,999	80	30-1/4"	77-1/4"	T85-400(A)	399,900	85	26-1/4"	78-13/16"
<b>L Series</b>									
D-100L-199	199,999	100	30-1/4"	74-3/4"	T100-200(A)	199,990	100	30-1/4"	73-1/16"
D-100L-250(A)	250,000	100	30-1/4"	74-3/4"	T100-250(A)	250,000	100	30-1/4"	73-1/4"
D-100L-270(A)	270,000	100	30-1/4"	74-3/4"	T100-270(A)	270,000	100	30-1/4"	73-7/8"
D-100L-300(A)	300,000	100	30-1/4"	75-1/2"	T100-310(A)	310,000	100	30-1/4"	75"
D-80L-399(A)	399,999	80	30-1/4"	71"	T65-400(A)	399,900	65	26-1/4"	70-11/16"
<b>TW Series</b>									
TW50T-65-3N	65,000	48	22"	66-1/4"	TPV75-75FV-2	75,000	75	26-1/4"	72"
TW75T-75-3N	75,000	75	26"	69-1/2"	TPV75-75FV-2	75,000	75	26-1/4"	72"
<b>High Efficiency Models</b>									
EF100T-150E-3N(A)	150,000	100	28-1/4"	78"	THE100-160(A)	160,000	100	26-1/4"	78-3/4"
EF100T-199E-3N(A)	199,999	100	28-1/4"	78"	THE100-200(A)	199,000	100	26-1/4"	78-3/4"
EF100T-250E-3N(A)	250,000	100	28-1/4"	78"	THE100-250(A)	250,000	100	26-1/4"	78-3/4"
EF100T-300E-3N(A)	300,000	100	28-1/4"	78"	THE100-300(A)	300,000	100	26-1/4"	78-3/4"
EF100T-399E-3N(A)	399,900	100	28-1/4"	78"	THE100-400(A)	399,900	100	26-1/4"	78-3/4"

NOTE: (A) denotes ASME construction available.

\*130-gallon models

Model	kW	Gal	Model	kW	Gal
<b>Electric – Light Duty and Point-of-Use Products</b>					
LD-6U3-1C015	1.5 Max	6	TEGSP6	6 Max	6
LD-12U3-1C015	1.5 Max	12	TEGSP10	6 Max	10
LD-20U3-1C015	6 Max	19	TEGSP20	6 Max	20
LD-30U3-1C015	6 Max	30	TEGSP30	6 Max	30
LD-30L3-3C045	12 Max	30	TELD530	12 Max	30
LD-40L3-3C045	12 Max	40	TELD540	12 Max	40
LD-50L3-3C045	12 Max	50	TELD552	12 Max	50
LD-WH6U3-1C015	1.5 Max	6	TEGSP6	6 Max	6
LD-WH12U3-1C015	1.5 Max	12	TEGSP10	6 Max	10
LD-WH20L3-1C015	6 Max	19	TEGSP20	6 Max	20
LD-WH30L3-1C015	6 Max	30	TEGSP30	6 Max	30
LD-40S3-3C045	12 Max	40	TELD40	12 Max	40
LD-50S3-3C045	12 Max	50	TELD52	12 Max	50
LD-65R3-3C045	12 Max	65	TELD66	12 Max	65
LD-80R3-3C045	12 Max	80	TELD80	12 Max	80
LC-120R3-3C045	12 Max	120	TELD120	12 Max	120

Continued next page.

## BRADFORD WHITE TO PERFECT FIT

Bradford White			Perfect Fit		
Model	kW	Gal	Model	kW	Gal
<b>Electric – Heavy Duty Products</b>					
HS*(kW)-052	9 to 36	52	TES50	6 to 54	50
12A-KW-3	3 to 9	12	TE12A	3 to 9	12
20A-KW-3	3 to 18	20	TE20A	3 to 18	20
30A-KW-3	3 to 36	30	TE30A	3 to 36	30
40A-KW-3	3 to 36	40	TE40A	3 to 36	40
M-II-50SF/CF	6 to 54	50	TES50/TE50	6 to 54	50
M-II-80SF/CF	6 to 54	80	TES85/TE85	6 to 54	85
M-II-120SF/CF(A)	6 to 54	119	TES120/TE120	6 to 54	120

NOTE: "SF" uses surface mounted thermostats. "CF" uses immersion thermostats.

NOTE: "TES" models use surface mounted thermostats. "TE" models use immersion thermostats.

NOTE: (A) refers to ASME availability. Limited to "TE" products.

Typical Perfect Fit Configuration: TE50-(kW) or TES50-(kW) If kW = 36; Example: TE50-36 or TES50-36

### Storage Tank Systems (\*\*Unfired Storage Vessels)

M-3-ST80R5	**	80	ST80(A)	**	80
M-3-ST120R5	**	119	ST120(A)	**	115
M-3-ST120R5(A)	**	119	ST120A	**	115
M-3-ST200R5(A)	**	200	ST175A	**	17

### Electric – Instantaneous/Booster Products

L-I-6-3CF	6 to 58	5	TE10	6 to 54	10
-----------	---------	---	------	---------	----

Typical Bradford White Configuration: L-I-6-(kW)-3CF Example: L-I-6-36-3CF