

12-Year Electric



▶ 12-Year Limited Warranty on Tank and Parts

- Rigid foam insulation for superior heat retention
- EverKleen™ self-cleaning system fights sediment build up
- LIFE GUARD™ longer life patented stainless steel upper heating element
- 5500 watt heating elements - heat water 22% faster than standard 4500 watt elements
- Heat trap and pipe insulation kit reduces convective heat loss for greater efficiency
- Heavy-duty anode rod for extended tank protection
- Porcelain lined tank surface for longer life
- Easy access thermostat adjustment
- Factory installed temperature and pressure relief valve
- Includes extra durable high temperature dip tube to meet the most stringent plumbing codes
- Meets or exceeds National Appliance Energy Conservation Act (NAECA) requirements

Energy Factor and Average Annual Operating Costs based on D.O.E. (Department of Energy) test procedures. The D.O.E. national average fuel rate for electricity is 10.65¢/kWh.

DESCRIPTION			FEATURES			DIMENSIONS				ENERGY INFORMATION	
Tank Gallon Capacity	Height Description	Model Number	Heating Element Watt. Upper	Heating Element Watt. Lower	First Hour Del. G.P.H.	Tank Diam.	Tank Height	Height to Water Conn.	Ship Wt. (Pounds)	Energy Factor	Est. Annual Oper. Costs
40	Medium	12EM40-2	5500	5500	53	19-3/4	46-1/2	46-1/2	95	0.92	\$508
50	Medium	12EM50-2	5500	5500	62	21-3/4	46	46	117	0.90	\$520
50	Tall	12E50-2	5500	5500	67	19	57	57	107	0.90	\$520
50	Medium	12EMR50-2†	5500	5500	62	24-1/4	46	46	128	0.93	\$503
65	Tall	12E65-2	5500	5500	71	21	58-1/2	58-1/2	150	0.89	\$525
80	Tall	12E80-2	5500	5500	88	23	59	59	177	0.86	\$544

• Water heaters furnished with standard 240 volt AC, single phase, non-simultaneous wiring.

† Electric utility model – qualifies for most electric rebate programs..