

# RUUD SALES FACT SHEET



## ACHIEVER® 90 PLUS HIGH EFFICIENCY DOWNFLOW/HORIZONTAL GAS FURNACES

### Features

- Heat exchanger is constructed of all stainless steel for maximum corrosion resistance and thermal fatigue reliability.
  - Low profile "34 inch" design is lighter and easier to handle and leaves room for optional accessories.
  - Top electrical connections, left or right gas and condensate drainage connections on downflow models.
  - Condensate drain for horizontal application provided standard.
  - Integrated control board manages all operational functions and provides hookups for humidifier and electronic air cleaner.
  - An insulated blower compartment, a slow-opening gas valve and a specially designed inducer system make it one of the quietest furnaces on the market today.
  - Pre-paint galvanized steel cabinet.
  - Molded permanent filters.
  - Optional indoor or outdoor combustion air.
  - Transformer and control fuse protection.
  - Control board diagnostics.
- A variety of cooling coils and plenums designed to use with the Achiever® 90 Plus gas furnaces are available as optional accessories for air conditioning models.

### RGTA- SERIES

Models with Input Rates  
from 45,000 to 120,000 BTU/HR  
[13.19 to 35.17 kW]

(All Models 90% A.F.U.E. or Above)

### GENERAL TERMS OF LIMITED WARRANTY

Ruud will furnish a replacement for any part of this product which fails in normal use and service within the applicable period stated, in accordance with the terms of the limited warranty.

Primary and Secondary Heat Exchanger . . . . . Limited Lifetime  
Conditional Parts\* (Registration Required) . . . . . Ten (10) Years

\*Refer to Product Warranty Card for details.

MODEL	INPUT- BTU/HR [kW] ①	HEATING CAPACITY BTU/HR [kW]	HEATING CFM @ .2" [.049 kPa] W.C. E.S.P. [L/s]	COOLING CFM @ .5" [.12 kPa] W.C. E.S.P. [L/s]	APPROX. SHIPPING WEIGHT (LBS.) [kg]	PRICE
RGTA-04EMAES	45,000 [13.19]	41,000 [12.02]	890 [420]	1220 [576]	111 [50.3]	
RGTA-06EMAES	60,000 [17.58]	56,000 [16.41]	885 [418]	1180 [557]	117 [53.1]	
RGTA-07EMAES	75,000 [21.98]	69,000 [20.22]	1060 [500]	1150 [543]	123 [55.8]	
RGTA-07EYBGS	75,000 [21.98]	69,000 [20.22]	1375 [649]	1625 [767]	123 [55.8]	
RGTA-09EZAJS	90,000 [26.38]	84,000 [24.62]	1400 [661]	1850 [873]	148 [67.1]	
RGTA-10EZAJS	105,000 [30.77]	97,000 [28.43]	1425 [673]	1820 [859]	152 [68.9]	
RGTA-12ERAJS	120,000 [35.17]	112,000 [32.82]	1565 [739]	2040 [963]	160 [72.6]	

① See Conversion Kit Index Form for high altitude derate.

