#### The new degree of comfort.™

# Warrior DVX are direct vent co-axial gas water heaters for manufactured housing that are FVIR compliant

# **Efficiency**


• .59 EF

#### **Performance**

- FHR: 78-gallons for 50-gallon model and 66-gallons for 40-gallon model
- Recovery rates: 36.4 for 40 and 50-gallon natural gas models at a 90 degree rise

### **Flexibility**

- Field convertible controls and burner assembly for natural gas or LP operation included
- Roof jack flange adjustment range available up to 34° (8 - 12)
- New smaller foot print no external air tube
- Can be installed anywhere in the home
- 3/4" hot and cold top connections
- Easily fits into a standard drain pan



# **Altitude Certification**

 All models certified up to 7,700 ft. above sea level

#### **Longer Life**

 Patented magnesium anode rod with resistor protects the tank from rust

# **Self Cleaning**

 EverKleen<sup>™</sup> patented system fights sediment build-up

# Plus...

- Certified for manufactured (HUD) and modular construction
- Factory installed temperature and pressure relief valve – side location
- Piezo ignition easy light pilot, no matches required

# Warranty

 1-Year limited tank, 1-year limited parts warranty\*

\*See Residential Warranty Certificate for complete information

Units meet or exceed ANSI requirements and have been tested according to D.O.E. procedures. Units meet or exceed the energy efficiency requirements of NAECA, ASHRAE standard 90, ICC Code and all state energy efficiency performance criteria.



# **Warrior DVX**

40 and 50-Gallon Capacities Up to 36,000 Btu/h








## **CO-AXIAL ROOF JACK SIZING TABLE**

| 34° MAX. (8-12<br>PITCH) ROOF JACK<br>KIT PART NUMBER | ROOF JACK<br>ADJUSTMENT<br>RANGE (SEE X) |
|-------------------------------------------------------|------------------------------------------|
| AP14363A                                              | 24 - 37 Inches                           |
| AP14363B                                              | 33 - 68 Inches                           |
| AP14363C                                              | 45 - 97 Inches                           |
| AP14363D                                              | 60 - 130 Inches                          |
| AP14363E                                              | 72 - 160 Inches                          |

NOTE: 42° Max. adjustment roof jacks available. Roof Jacks must be ordered separately with this direct vent water heater and installed in accordance with the instructions furnished with the heater. No other roof jack or vertical vent kit is approved for installation with this heater.



|             | I    | DESCRIPTION  | FEATURES                     |    |                                |                           |       | ROUGHING IN DIMENSIONS (SHOWN IN INCHES) |              |       |              |                  | ENERGY INFORMATION       |       |       |
|-------------|------|--------------|------------------------------|----|--------------------------------|---------------------------|-------|------------------------------------------|--------------|-------|--------------|------------------|--------------------------|-------|-------|
| T<br>Y<br>P | GAL. |              | GAS INPUT IN<br>THOUS. BTU/H |    | RECOVERY IN<br>G.P.H. 90° RISE | FIRST HOUR<br>DEL. G.P.H. | DIAM. | TANK<br>HEIGHT                           | VENT<br>SIZE | WATER | SHIP.<br>WT. | ENERGY<br>FACTOR | AVG. ANN.<br>OPER. COSTS |       |       |
| Ē           | CAP. | MODEL NUMBER | NAT.                         | LP | NAT.                           | LP                        | NAT.  | A                                        | В            | С     | CONNECTION   | (LBS)            | NAT/LP                   | NAT.  | LP    |
| T<br>A      | 40   | 22I40FDVX    | 36                           | 30 | 36.4                           | 30.3                      | 66    | 19-3/4                                   | 59-3/4       | 5     | 3/4          | 155              | 0.59                     | \$309 | \$520 |
| F           | 50   | 22I50FDVX    | 36                           | 32 | 36.4                           | 32.3                      | 78    | 21-3/4                                   | 59-1/2       | 5     | 3/4          | 165              | 0.59                     | \$309 | \$520 |

Energy Factor and Average Annual Operating Costs based on D.O.E. (Department of Energy) test procedures. D.O.E. national average fuel rate natural gas \$1.218/therm; LP \$1.87/gallon.

In keeping with its policy of continuous progress and product improvement, Rheem reserves the right to make changes without notice.

Rheem Water Heating • 101 Bell Road Montgomery, Alabama 36117-4305 • www.rheem.com Rheem Canada Ltd./Ltée • 125 Edgeware Road, Unit 1 Brampton, Ontario L6Y 0P5 • www.rheem.com

