



SALES FACT SHEET



RQNJ- SUPER HIGH EFFICIENCY SERIES

13 SEER Series

Nominal Sizes 2-5 Tons [7-17.6 kW]

GENERAL TERMS OF LIMITED WARRANTY

Rheem will furnish a replacement for any part of this product which fails in normal use and service within the applicable period stated, in accordance with the terms of the limited warranty.

CompressorFive (5) Years
*Any Other PartFive (5) Years

*All other parts and components carry a limited warranty of five years, provided they are single-phase products installed in a residential application. Products installed in commercial applications have a one (1) year limited parts warranty.

Classic® S E R I E S

Features

The *Rheem Classic® Series* RQNJ- Dedicated Horizontal Heat Pump units can provide year-round heating and cooling comfort for residential, multi-family and light commercial applications.

The following additional features, plus its energy-saving characteristics, make the RQNJ- Heat Pump unit an excellent choice for new construction or upgrading your present system.

- Scroll Compressor
- Copper Tube/Aluminum Fin Coils
- Powder painted louvered steel cabinet protects coil from damage
- Painted Base Pan
- Demand Defrost Control
- Non-Cycling Reversing Valve
- Gauge Ports
- Control box is fully accessible
- Power and control wiring are kept separate
- Certified and rated under ARI Standard 240
- U.L. listed

<u>R</u>	<u>Q</u>	<u>N</u>	<u>J</u>	<u>—</u>	<u>A</u>	<u>036</u>	<u>J</u>	<u>K</u>	<u>010</u>
RHEEM	PRODUCT CLASSIFICATION	EFFICIENCY DESIGNATION (STANDARD)	DESIGN SERIES		FUTURE TECHNICAL VARIATIONS	COOLING CAPACITY	ELECTRICAL DESIGNATION	DRIVE PACKAGE	HEATING CAPACITY (RESISTANCE HEAT)
	Q = PACKAGE HEAT PUMP	N = 13 SEER	J = HORIZONTAL DISCHARGE			024 = 24,000 BTU/H [7.03 kW] 030 = 30,000 BTU/H [8.79 kW] 036 = 36,000 BTU/H [10.55 kW] 042 = 42,000 BTU/H [12.31 kW] 048 = 48,000 BTU/H [14.07 kW] 060 = 60,000 BTU/H [17.58 kW]	J = 208-230V— 1PH—60 Hz	K = DIRECT DRIVE	000 = NONE 005 = 05 KW 007 = 07 KW 010 = 10 KW 015 = 15 KW 020 = 20 KW

Price

Starting at:
\$

