

Encore 64 Mid-Efficiency Tankless Gas For 1-2 Bathroom Homes*



150,000 BTU/H
INDOOR DI-
RECT VENT

150,000 BTU/H
OUTDOOR

RMTG-64DVL indoor direct vent and RMTG-64XL outdoor natural and LP models – 11,000 - 150,000 Btu/h max.

6.4 gal./min at 35° F rise max.,
5.6 gal./min. at 45° F rise

Limited Warranty:

12-Year on heat exchanger, 5-Year on parts, 1-Year on labor

See Residential Warranty Certificate for complete warranty information.

- 3"/5" Concentric Vent System with Intergrated Condensate Collector
- Connects to Metal Fab Inc., 3"/5" Concentric Venting without an adapter
- Next Generation Burner Technology
- **Industry Best!** .26 GPM Minimum Flow Rate, .40 GPM Minimum Activation Flow Rate
- UMC-117 remote control and 10 ft. of thermostat wire is included

- EZ-Link™ cable available for high demand applications to connect two tankless units to operate as one
- Manifold up to 6 units with an optional MIC-6 manifold control board
- Manifold up to 20 units with the optional MIC-185 plus the MICS-180 manifold control assembly
- **Exclusive!** High-altitude capability – up to 9,840 ft. elevation above sea level
- **Exclusive!** OFW™ overheat film wrap
- All Encore tankless models are third-party efficiency certified by GAMA
- Continuous hot water, energy saving and compact, space saving design
- Intelligent electronic controls designed to increase energy efficiency and safety
- Self Diagnostic System
- Digital display shows temperature setting and maintenance codes
- Built-in electric blower
- Supplied with a 120 volt power cord
- Environmentally friendly Low NOx burner meets SCAQMD rule 1146 requirements
- Freeze protection to -30° F

Product appearance may differ.

* Based on simultaneous showers using 2.5 gallons per minute. Flow rates vary depending on temperature of cold water supply.

Energy Factor and Average Annual Operating Costs based on D.O.E. (Department of Energy) test procedures. D.O.E. national average fuel rate natural gas \$1.218/therm; LP \$1.87/gallon.

DESCRIPTION			FEATURES				DIMENSIONS					ENERGY INFO.			
MODEL NUMBER	GAS INPUT BTU/H	TYPE	TEMP. RANGE	WATER FLOW RATE			CONNECTION		HEIGHT	WIDTH	DEPTH	VENT	SHIP. WEIGHT (LBS.)	ENERGY FACTOR	EST. ANN. OPERATING COST
				GPM @ 77° RISE MAX.	GPM @ 45° RISE MAX.	GPM @ 35° RISE MAX.	WATER	GAS							
★ RMTG-64DVLN (NAT. GAS)	11,000 - 150,000	Indoor Direct Vent	100° to 140° F	3.3	5.6	6.4	3/4	3/4	25-5/8	13-7/8	9-7/8	3 by 5 CONCENTRIC	54	.82	\$223/374 NAT / LP
★ RMTG-64XLN (NAT. GAS)	11,000 - 150,000	Outdoor	100° to 140° F	3.3	5.6	6.4	3/4	3/4	23-5/8	13-7/8	8-7/8	N/A	54	.82	\$223/374 NAT / LP

- All models are available in Natural Gas and Propane (LP). For Propane replace the N with P when ordering.
- UMC-117 remote control is included and can be set from the out-of-the-box 120 degrees – up to a 140 degree maximum (additional remote control thermostats are available – sold separately)
- For installations above 3,200 feet, a high altitude chip is required. Refer to Richmond price list or consult factory for details.
- Consult factory for information on sizing the application.



Look for the ★ next to our new **ENERGY STAR®** compliant models for the ultimate in energy efficiency!