



SUBMITTAL COVER SHEET

PROJECT NAME _____

LOCATION _____

ARCHITECT _____

ENGINEER _____

CONTRACTOR _____

SUBMITTED BY _____ DATE _____

UNIT SUMMARY

Quantity						
Unit Designation						
Model No.						
Total Cooling						
Sensible Cooling						
Air Ent. Evaporator						
Air Lvg. Evaporator						
Heating Input						
Heating Output						
CFM/ESP						
EER/SEER						
Electrical						
Minimum Ampacity						
Min.-Max. Breaker						
Net Unit Weight						
Accessory						
Catalog Form Number						

ACCESSORIES:

NOTES:

SUBMITTAL SHEET FOR RGLN- 80% A.F.U.E. DOWNFLOW GAS FURNACES

**RGLN- Models with Input Rates from 50,000 to 150,000 BTU/HR
[15 to 44 kW].**

JOB NAME _____ MODEL NO. _____
CONTRACTOR _____ OUTDOOR UNIT MODEL NO. _____
ENGINEER _____ LOCATION _____
SUBMITTED FOR ☐ APPROVAL ☐ RECORD ORDER NO. _____
DATE _____

UNIT DATA

HEATING PERFORMANCE

TOTAL CAPACITY INPUT* MBH [kW]
TOTAL CAPACITY OUTPUT* .. MBH [kW]
DESIGN TEMP. RISE °F [°C] DB
AFUE %
CALIFORNIA SEASONAL
EFFICIENCY %
(*uses blower motor heat)

SUPPLY AIR BLOWER PERFORMANCE

TOTAL AIR SUPPLY CFM [L/s]
TOTAL RESISTANCE EXTERNAL
TO UNIT IWG
BLOWER SPEED RPM
POWER OUTPUT REQUIREMENT .. BHP
MOTOR RATING HP [W]
POWER INPUT REQUIREMENT kW

ELECTRICAL DATA

POWER SUPPLY Hz
TOTAL UNIT AMPACITY AMPS
MINIMUM WIRE SIZE AWG
MAXIMUM OVERCURRENT DEVICE
FUSES/HACR BREAKER AMPS

CLEARANCES

FRONT SIDE 3" [76.2 mm]
RIGHT SIDE 3" [76.2 mm]
LEFT SIDE 0" [0 mm]
TOP 1" [25.4 mm]

FEATURES FOR RGLN-

- Innovative design results in reliable, efficient operation at sound levels which provide distinct competitive advantage.
- Patented heat exchanger, constructed of both stainless and aluminized steel for the maximum in corrosion resistance.
- Low profile "34 inch" design is lighter and easier to handle, and leaves room for optional equipment.
- Left or right side gas and electric inlet connections with quick, simple change.
- Direct spark ignition.
- An integrated board with humidifier and electronic air cleaner hookups.
- Insulated blower compartment, a slow-open gas valve and a specially designed draft inducer motor make it one of the quietest furnaces on the market today.
- Pre-painted galvanized steel cabinet.
- Molded permanent filter.
- Grab-holes in doors to aid in easy door removal and replacement.

FIELD INSTALLED ACCESSORIES

- Plenum Adapter (RXAA-) ☐
Fossil Fuel Kit (RXPF-F01 and F02) ☐
Filter Rack (RXGF-CC*) ☐
*Filters available through PROSTOCK®
Combustible Floor Base (RXGC-B14, 17, 21, 24) ☐
High Altitude Kit (RXGY-F13 for two-stage models) ☐



DOWNFLOW MODELS




TABLE 1. DIMENSIONS AND CLEARANCE TO COMBUSTIBLE MATERIAL RGLN- MODELS (INCHES) [mm]

MODEL RGLN- SERIES	A	B	C	D	E	REDUCED CLEARANCES (IN.) [mm]						SHIP. WGTs. (LBS.) [kg]
						LEFT SIDE	RIGHT SIDE	BACK	TOP	FRONT	VENT	
05	14 [356]	12 27/32 [326]	10 3/8 [264]	①	13 1/8 [333]	0	4 [102] ②	0	1 [25]	3 [76]	6 [152] ③	85 [38.6]
07	17 1/2 [445]	16 11/32 [415]	12 1/8 [308]	①	16 5/8 [422]	0	3 [76] ②	0	1 [25]	3 [76]	6 [152] ③	105 [47.6]
10 (A)	17 1/2 [445]	16 11/32 [415]	12 1/8 [308]	①	16 5/8 [422]	0	3 [76] ②	0	1 [25]	3 [76]	6 [152] ③	115 [52.2]
10 (B)	21 [533]	19 27/32 [504]	13 7/8 [352]	①	20 1/8 [511]	0	0	0	1 [25]	3 [76]	6 [152] ③	120 [54.4]
12	24 1/2 [622]	23 11/32 [593]	15 5/8 [397]	①	23 5/8 [600]	0	0	0	1 [25]	3 [76]	6 [152] ③	140 [63.5]
15	24 1/2 [622]	23 11/32 [593]	15 5/8 [397]	①	23 5/8 [600]	0	0	0	1 [25]	3 [76]	6 [152] ③	150 [68]

NOTES: ① May require a 3" [76 mm] to 4" [102 mm] or 3" [76 mm] to 5" [127 mm] adapter.

② May be 0" [0 mm] with type B vent.

③ May be 1" [25 mm] with type B vent.


Furnaces must be vented in accordance with ANSI Z21.47-1993 • CAN/CGA-2.3-M93 venting table guidelines included with each furnace, and in accordance with local codes.

[] Designates Metric Conversions

DOWNFLOW WARNING: Unit design is certified for installation on non-combustible floor. A special factory supplied combustible floor sub-base is required when installing on a combustible floor. Failure to install the sub-base may result in fire, property damage and personal injury.

COMBUSTIBLE FLOOR BASE DIMENSIONS

COMBUSTIBLE FLOOR BASE	USE WITH FURNACE SIZES	A IN. [mm]	B IN. [mm]	C IN. [mm]
RXGC-B14	(-)GLN-05	14 1/2 [368]	13 1/4 [337]	11 1/4 [286]
RXGC-B17	(-)GLN-07, (-)GLN-10(-)A	18 [457]	16 3/4 [425]	14 3/4 [451]
RXGC-B21	(-)GLN-10(-)B	21 1/2 [546]	20 1/4 [514]	18 1/4 [464]
RXGC-B24	(-)GLN-12, (-)GLN-15	25 [635]	23 3/4 [603]	21 3/4 [552]



Before proceeding with installation, refer to installation instructions packaged with each model, as well as complying with all Federal, State, Provincial, and Local codes, regulations, and practices.

Rheem Sales Company, Inc.
P.O. Box 17010, Fort Smith, AR 72917

"In keeping with its policy of continuous progress and product improvement, Rheem reserves the right to make changes without notice."