

RUUD SALES FACT SHEET



RUUD ACHIEVER® SERIES 95% A.F.U.E. with DUAL COMFORT CONTROL™ TWO-STAGE DOWNFLOW/HORIZONTAL GAS FURNACES



"Visit www.Ruud.com for complete details."

All Models 95% A.F.U.E. or Above

RGTM- SERIES

ECM Equipped

Models with Input Rates of 60,000, 75,000, 90,000 & 105,000 BTU/HR [17.58, 22, 26.38 & 30.77 kW]

GENERAL TERMS OF LIMITED WARRANTY

Ruud will furnish a replacement for any part of this product which fails in normal use and service within the applicable period stated, in accordance with the terms of the limited warranty.

Primary and Secondary Heat Exchanger Limited Lifetime
 Conditional Parts Warranty
 (Registration Required) Ten (10) Years
 Conditional Unit Replacement Warranty
 (Registration Required) Ten (10) Years

Features

- Two stages of operation to save energy and maintain optimal comfort level.
- Furnace operates at 70% capacity for low-heat and 100% capacity for high-heat.
- Compatible with single or two-stage thermostat. (For optimal performance a two-stage thermostat is recommended.)
- Heat exchanger is constructed of all stainless steel for maximum corrosion resistance and thermal fatigue reliability.
- Low profile "34 inch" design is lighter and easier to handle and leaves room for optional accessories.
- Left or right side gas, electric, and condensate drainage connections.
- Integrated control board manages all operational functions and provides hookups for humidifier and electronic air cleaner.
- An insulated blower compartment, a slow-opening gas valve and a specially designed inducer system make it one of the quietest furnaces on the market today.
- Variable speed blower motor technology provides ultimate humidity control, quieter sound levels and year-round energy savings.
- Optional indoor or outdoor combustion air. In addition, combustion air may be piped to either the top or side of the cabinet on all downflow models. A special molded fitting is provided to ease installation.
- Control fuse protection.
- Solid bottom is standard.
- Control board diagnostics.

A variety of cooling coils and plenums designed to use with the Ruud Achiever® Series 95% A.F.U.E. gas furnaces are available as optional accessories for air conditioning models.

MODEL	HIGH FIRE INPUT BTU/HR [kW]	LOW FIRE INPUT BTU/HR [kW]	HIGH HEATING CFM @ .2" [.049 kPa] W.C. E.S.P. [L/s]	HIGH COOLING CFM @ .8" [.124 kPa] W.C. E.S.P. [L/s]	APPROX. SHIPPING WEIGHT (LBS. [kg])	PRICE
RGTM-06*MAES	60,000 [17.58]	42,000 [12.31]	900 [425]	1200 [566]	123 [56.0]	
RGTM-07*RBGS	75,000 [21.98]	52,500 [15.39]	1180 [510]	1600 [755]	123 [56.0]	
RGTM-09*Zajs	90,000 [26.38]	63,000 [18.46]	1450 [684]	2000 [944]	148 [67.5]	
RGTM-10*RBJS	105,000 [30.77]	73,500 [21.60]	1604 [757]	2000 [944]	165 [75.0]	

*E=Standard, N=NOx Models

[] Designates Metric Conversions

