

9-Year Gas



▶ 9-Year Limited Warranty on Tank and Parts

Integra System™

- One-of-a-kind air/fuel shut-off device offers double protection
- Maintenance free – no filter to clean
- Standard replacement parts

Environmentally Friendly Burner

- Low NOx design for low nitrous oxide emissions

Self-Cleaning

- EverKleen™ patented system fights sediment build-up
- Reduces fuel costs
- Provides more hot water

Easy to Light

- No matches required

Energy Efficient

- More hot water at low operating cost

Longer Life

- Patented magnesium anode rod design incorporates a special resistor that protects the tank from rust

High Altitude Compliant

- All models are certified for applications up to 6,000 feet above sea level. Some models are certified up to 10,200 feet above sea level. Check factory for listing

Plus...

- Temperature and pressure relief valve is included
- Specially formulated glass lining prevents corrosion and extends the life of the tank
- Meets or exceeds National Appliance Energy Conservation Act (NAECA) requirements

Energy Factor and Average Annual Operating Costs based on D.O.E. (Department of Energy) test procedures. The D.O.E. national average fuel rate is \$1.218/therm for natural gas and \$1.87/gallon for LP gas.

DESCRIPTION			FEATURES				DIMENSIONS					ENERGY INFORMATION		
Tank Gallon Capacity	Height Description	Model Number	Thous. Btu/h Nat.	LP	Recovery in G.P.H. 90° Rise	First Hour Del. G.P.H.	Tank Diam.	Vent Height	Tank Height	Vent Size	Shipping Wt. (Pounds)	Energy Factor	Est. Ann. Operating Cost Nat.	Operating Cost LP
40	Short	9G40S-40F1	40	–	40.4	72	20-1/8	53-7/8	50-1/2	3 or 4	130	0.59	\$309	–
40	Tall	9G40-38F1	38	–	38.4	73	18-1/8	61-3/4	58-3/8	3 or 4	120	0.59	\$309	–
50	Tall	9G50-38F1	38	–	38.4	90	20-1/8	61-1/2	58-1/4	3 or 4	130	0.58	\$315	–

• Above natural gas fired models meet 40ng/J NOx requirements.