

RUUD SALES FACT SHEET



"Visit www.Ruud.com for complete details."

RUUD ACHIEVER® SERIES 90 PLUS with DUAL COMFORT CONTROL™ TWO-STAGE UPFLOW GAS FURNACES

All Models 95% A.F.U.E. or Above

Features

- Two stages of operation to save energy and maintain optimal comfort level.
- Furnace operates at 70% capacity for low-heat and 100% capacity for high-heat.
- Compatible with single or two-stage thermostat. (For optimal performance a two-stage thermostat is recommended.)
- Heat exchanger is constructed of all stainless steel for maximum corrosion resistance and thermal fatigue reliability.
- Low profile "34 inch" design is lighter and easier to handle and leaves room for optional accessories.
- Left or right side gas, electric, and condensate drainage connections.
- Integrated control board manages all operational functions and provides hookups for humidifier and electronic air cleaner.
- An insulated blower compartment, a slow-opening gas valve and a specially designed inducer system make it one of the quietest furnaces on the market today.
- Features a Limited Lifetime Warranty on the primary and secondary heat exchanger and a 10-Year Limited Warranty on all other parts.
- Molded permanent filters.
- Optional indoor or outdoor combustion air. In addition, combustion air may be piped to either the top or side of the cabinet on all upflow models. A special molded fitting is provided to ease installation.
- Dual certified for sealed combustion (2-pipe) or non-direct (1-pipe) applications.
- Solid bottom is standard.
- Control board diagnostics.

A variety of cooling coils and plenums designed to use with the Ruud Achiever® Series 90 Plus gas furnaces are available as optional accessories for air conditioning models.

RGRL- SERIES

Models with Input Rates of
45,000, 60,000, 75,000,
90,000 & 105,000 BTU/HR
[13.19, 17.58, 22, 26.38 & 30.77 kW]

GENERAL TERMS OF LIMITED WARRANTY

Ruud will furnish a replacement for any part of this product which fails in normal use and service within the applicable period stated, in accordance with the terms of the limited warranty.

Primary and Secondary Heat Exchanger Limited Lifetime
Conditional Parts Warranty
(Registration Required) Ten (10) Years

MODEL	HIGH FIRE INPUT BTU/HR [kW]	LOW FIRE INPUT BTU/HR [kW]	HEATING CFM @ .2" [.049 kPa] W.C. E.S.P. [L/s]	COOLING CFM @ .5" [.124 kPa] W.C. E.S.P. [L/s]	APPROX. SHIPPING WEIGHT (LBS. [kg])	PRICE
RGRL-04*MAES	45,000 [13.19]	31,500 [9.23]	885 [417]	1195 [564]	111 [50.3]	
RGRL-06*MAES	60,000 [17.58]	42,000 [12.31]	845 [398]	1100 [519]	117 [53.1]	
RGRL-07*MAES	75,000 [21.98]	52,500 [15.39]	1050 [495]	1110 [524]	123 [55.8]	
RGRL-07*YBGS	75,000 [21.98]	52,500 [15.39]	1275 [600]	1540 [725]	145 [65.5]	
RGRL-09*ZAJ5	90,000 [26.38]	63,000 [18.46]	1465 [691]	1910 [901]	148 [67.1]	
RGRL-10*ZAJ5	105,000 [30.77]	73,500 [21.40]	1445 [682]	1810 [854]	152 [69]	

*E=Standard, N=NOx Models

[] Designates Metric Conversions

