



SALES FACT SHEET



Features

- Coils constructed with copper tubing and enhanced aluminum fins.
- Strong, attractive cabinet—louvered design protects the coil from damage.
- Expansion Valves with Internal Check Valve—Provides for quieter refrigerant metering.
- Demand Defrost Control
- Non-Cycling Reversing Valve
- Hot Gas Muffler
- Service Valves
- Grille/motor mount for quiet fan operation.
- Easily accessible control box.
- Certified and rated under ARI Standard 240.
- U.L. listed.

GENERAL TERMS OF LIMITED WARRANTY

ICECOSM will furnish a replacement for any part of this product which fails in normal use and service within the applicable periods stated, in accordance with the terms of the limited warranty.

Condenser Coil leaks caused by
 factory defectsFive (5) Years
 CompressorFive (5) Years
 Any Other PartFive (5) Years

13PJA SERIES

<u>13</u>	<u>P</u>	<u>J</u>	<u>A</u>	<u>—</u>	<u>18</u>	<u>A</u>	<u>01</u>
13 SEER	P = HEAT PUMP	VOLTAGE	DESIGN SERIES	NOMINAL COOLING CAPACITY	CABINET	RHEEM VALUE SERIES	
		J = 208-230 SINGLE PHASE	A = 1ST DESIGN	18 = 18,000 BTU/HR [5.28 kW] 24 = 24,000 BTU/HR [7.03 kW] 30 = 30,000 BTU/HR [8.79 kW] 36 = 36,000 BTU/HR [10.55 kW] 42 = 42,000 BTU/HR [12.31 kW] 48 = 48,000 BTU/HR [14.07 kW] 60 = 60,000 BTU/HR [17.58 kW]	A = FULL METAL JACKET		

Price	Starting at: \$
-------	--------------------

