



# SALES FACT SHEET



Featuring  
Earth-Friendly  
R-410A Refrigerant

**R-410A**  
earth friendly refrigerant



## 14PJL SERIES

<b>14</b>	<b>P</b>	<b>J</b>	<b>L</b>
14 SEER	P = HEAT PUMP	VOLTAGE J = 208-230 SINGLE PHASE	DESIGN SERIES L = R-410A

## Features

- Coils constructed with copper tubing and enhanced aluminum fins
- Strong, attractive cabinet—louvered design protects the coil from damage
- Expansion Valves with Internal Check Valve—provides for quieter refrigerant metering
- Demand Defrost Control
- Non-Cycling Reversing Valve
- Hot Gas Muffler
- Service Valves
- Grille/motor mount for quiet fan operation
- Easily accessible control box
- Bi-Directional Filter Drier (shipped – not installed)
- Certified and rated under ARI Standard 240
- U.L. listed

## GENERAL TERMS OF LIMITED WARRANTY

Rheem will furnish a replacement for any part of this product which fails in normal use and service within the applicable periods stated, in accordance with the terms of the limited warranty.

Condenser Coil leaks caused by

factory defects	.....Five (5) Years
Conditional Compressor*	.....Ten (10) Years
Any Other Part	.....Five (5) Years

\*See Product Warranty Card for Details.

<b>18</b>	<b>A</b>	<b>01</b>
NOMINAL COOLING CAPACITY	CABINET	RHEEM VALUE SERIES
18 = 18,000 BTU/HR [5.28 kW]	A = FULL METAL JACKET	
24 = 24,000 BTU/HR [7.03 kW]		
30 = 30,000 BTU/HR [8.79 kW]		
36 = 36,000 BTU/HR [10.55 kW]		
42 = 42,000 BTU/HR [12.31 kW]		
48 = 48,000 BTU/HR [14.07 kW]		
60 = 60,000 BTU/HR [17.58 kW]		

Price	Starting at:
	\$

