

UUD SALES FACT SHEET



AIR HANDLERS

RHSA- Standard Efficiency
featuring R-22 Refrigerant
RHSL- Standard Efficiency
featuring New Industry Standard
R-410A Refrigerant



Features

- 1¹/2 ton [5.3 kW] through 5 ton [17.6 kW] models are between 42¹/2 to 55¹/2 inches [1080 to 1410 mm] tall and 22 inches [559 mm] deep.
- Versatile 4-way convertible design for upflow, downflow, horizontal left and horizontal right applications.
- Factory-installed high efficiency indoor coil.
- All models meet or exceed 330 to 400 CFM [156 to 189 L/s] per ton at .3 inches [.7 kPa] of external static pressure.
- Enhanced airflow up to .7" external static pressure.
- Sturdy construction with 1.0 inch [.24 kPa] of reinforced foil faced jacket insulation for excellent thermal and sound insulation.
- Field-installed auxiliary electric heater kits provide exact heat for indoor comfort. Kits include circuit breakers which meet UL and cUL requirements for service disconnect.

GENERAL TERMS OF LIMITED WARRANTY

Ruud will furnish a replacement for any part of this product which fails in normal use and service within the applicable period stated, in accordance with the terms of the limited warranty.

<u>n</u>	<u>п</u>
RUUD	CLASSIFIC

CLASSIFICATION

H =

AIR HANDLER

<u>**S**</u> S =

STANDARD

MODEL

(PSC MOTOR)

A —

REFRIGERANT

L = R-410A

A = R-22

НМ

A/C OR HP MULTI-POSITION

(VERTICAL UPFLOW/ HORIZONTAL LEFT IS THE FACTORY CONFIGURATION)

24

<u>CAPACITY</u> 18 = 18,000 BTU/HR [5.27 kW]

24 = 24,000 BTU/HR [7.03 kW]

30 = 30,000 BTU/HR [8.79 kW] 36 = 36,000 BTU/HR

[10.55 kW] 42 = 42,000 BTU/HR [12.31 kW] 48 = 48,000 BTU/HR

[14.06 kW] 60 = 60,000 BTU/HR [17.58 kW]

<u>17</u>

CABINET <u>SIZE</u> = 17 5" [431

17 = 17.5" [431.8 mm] (800-1200 CFM) 21 = 21" [533.4 mm]

(1400-1600 CFM) 24 = 24.5" [609.6 mm] (1600-1800 CFM)

J

D = 480/3/60

J = 208/240/1/60

<u>VOLTAGE</u> A =115/1/60

DESIGN VARIATION A =

Α

A = 1ST DESIGN

Price Starting at:







