



# SALES FACT SHEET



## Classic<sup>®</sup> S E R I E S



### 90 PLUS<sup>®</sup> with *DUAL COMFORT CONTROL* TWO-STAGE DOWNFLOW/ HORIZONTAL GAS FURNACES

#### Features

- Two stages of operation to save energy and maintain optimal comfort level.
- Furnace operates at 70% capacity for low-heat and 100% capacity for high-heat.
- Compatible with single or two-stage thermostat. (For optimal performance two-stage thermostat recommended.)
- Heat exchanger tubular construction is stainless steel for maximum corrosion resistance and thermal fatigue reliability.
- Low profile "34 inch" design is lighter and easier to handle and leaves room for optional accessories.
- Top electrical connections, left or right side gas, electric, and condensate drainage connections on downflow/horizontal models.
- Integrated control board manages all operational functions and provides hookups for humidifier and electronic air cleaner.
- An insulated blower compartment, a slow-opening gas valve and a specially designed inducer system make it one of the quietest furnaces on the market today.
- Pre-paint galvanized steel cabinet.
- Molded permanent filters.
- Optional indoor or outdoor combustion air.
- Transformer and control fuse protection.
- Control board diagnostics.
- Condensate drain trap for horizontal/downflow application provided standard.

A variety of cooling coils and plenums designed to use with the Classic 90 Plus gas furnaces are available as optional accessories for air conditioning models.

#### RGTK- SERIES

Models with Input Rates  
from 60,000 to 120,000 BTU/HR  
[17.58 to 35.17 kW]

(All Models 92% A.F.U.E. or Above)

#### GENERAL TERMS OF LIMITED WARRANTY

Rheem will furnish a replacement for any part of this product which fails in normal use and service within the applicable period stated, in accordance with the terms of the limited warranty.

Primary and Secondary Heat Exchanger . . . . . Limited Lifetime  
\*Any Other Part . . . . . Five (5) Years

\*This five year limited warranty is applicable only to single-phase products installed in residential applications.

MODEL	HIGH FIRE INPUT BTU/HR [kW]	LOW FIRE INPUT BTU/HR [kW]	HEATING CFM @ .2" [.049 kPa] W.C. E.S.P. [L/s]	COOLING CFM @ .5" [.124 kPa] W.C. E.S.P. [L/s]	APPROX. SHIPPING WEIGHT (LBS. [kg])	PRICE
RGTK-06*MAES	60,000 [17.58]	42,000 [12.31]	885 [418]	1180 [557]	117 [53.1]	
RGTK-07*MAES	75,000 [21.98]	52,500 [15.39]	1060 [500]	1150 [543]	123 [55.8]	
RGTK-07*YBGS	75,000 [21.98]	52,500 [15.39]	1375 [649]	1625 [767]	123 [55.8]	
RGTK-09*ZAJA	90,000 [26.38]	63,000 [18.46]	1400 [661]	1850 [873]	148 [67.1]	
RGTK-10*ZAJA	105,000 [30.77]	73,500 [21.54]	1425 [673]	1820 [859]	152 [68.9]	
RGTK-12*RAJS	120,000 [35.17]	84,000 [24.62]	1565 [739]	2040 [963]	160 [72.6]	

\*E=Standard, N=NOx Models

