

RUUD SALES FACT SHEET

UANL- SERIES

Efficiencies up to 14.50 SEER/12.50 EER

Nominal Sizes 1.5 to 5 Ton

[5.28 to 17.6 kW]

Cooling Capacities 18.3 to 62 kBTU

[5.36 to 18.17 kW]



Ruud Achiever® Series™ Air Conditioners

Features

The Ruud Achiever® Series High Efficiency UANL- Condensing Units were designed with performance in mind. These units offer comfort, energy conservation and dependability for single, multi-family and light commercial applications.

- Attractive, louvered wrap-around jacket protects the coil from yard hazards and weather extremes. Top grille is steel reinforced for extra strength. Cabinet is powder painted for all-weather protection.
- Air is discharged upward away from bushes and shrubs. The discharge pattern of the top grille provides minimum air restriction.
- Combination Grille/Motor Mount secures the motor to the underside of the discharge grille. The grille protects the motor windings and bearings from rain and snow.
- All controls are accessible by removing one service panel. Removable top grille provides access to the condenser fan motor and condenser coil.
- Single speed 8-pole fan motor designed for low speed, quiet, energy-saving operation.
- All models meet or exceed a 1000-hour salt spray test per ASTM B117 Standard Practice for Operating Salt Spray Testing Apparatus.


GENERAL TERMS OF LIMITED WARRANTY*

Ruud will furnish a replacement for any part of this product which fails in normal use and service within the applicable period stated, in accordance with the terms of the limited warranty.

Conditional Parts (Registration Required)Ten (10) Years

*For complete details of the Limited and Conditional Warranties, including applicable terms and conditions, contact your local contractor or the Manufacturer for a copy of the product warranty certificate.

Model	Nominal Cooling Capacity (BTU/HR)	Voltage	Phase	Height	Width	Length	Shipping Weight	Service Valve - Liquid	Service Valve - Suction	Price
018	18,000 [5.28 kW]	208/230	1	19 [483]	23 ³ / ₄ [603]	35 ¹ / ₂ [902]	140	3/8"	3/4"	
024	24,000 [7.03 kW]	208/230	1	19 [483]	27 ⁵ / ₈ [702]	40 ¹ / ₂ [1029]	150	3/8"	3/4"	
031	30,000 [8.79 kW]	208/230	1	19 [483]	27 ⁵ / ₈ [702]	40 ¹ / ₂ [1029]	152.5	3/8"	3/4"	
037CAZ	36,000 [10.55 kW]	208/230	1	23 [584]	31 ¹ / ₂ [800]	44 ³ / ₈ [1127]	211.5	3/8"	3/4"	
037DAZ		208/230	3							
037JAZ		460	3							
043CAZ	42,000 [12.31 kW]	208/230	1	23 [584]	31 ¹ / ₂ [800]	44 ³ / ₈ [1127]	210.5	3/8"	3/4"	
043DAZ		208/230	3							
043JAZ		460	3							
049CAZ	48,000 [14.07 kW]	208/230	1	29 [737]	31 ¹ / ₂ [800]	44 ³ / ₈ [1127]	233.5	3/8"	7/8"	
049DAZ		208/230	3							
049JAZ		460	3							
049YAZ		575	3							
060CAZ	60,000 [17.58 kW]	208/230	1	33 [383]	31 ¹ / ₂ [800]	44 ³ / ₈ [1127]	260	3/8"	7/8"	
060DAZ		208/230	3							
060JAZ		460	3							
060YAZ		575	3							



"Proper sizing and installation of equipment is critical to achieve optimal performance. Ask your Contractor for details or visit www.energystar.gov."



SALES FACT SHEET

ACCESSORIES

Description	Part No.	Price
Low Ambient Control (RXAD-A08)	RXAD-A08	
Crankcase Heater for 1.5 - 3 ton Models	44-17402-44	
Crankcase Heater for 3.5 - 5 ton Models	44-101884-01	
Compressor Time Delay	RXMD-B01	

Total Price

\$