



SALES FACT SHEET



ACHIEVER[®] Series

Features

The Ruud *Achiever Series*[®] and UPNL- Heat Pump Outdoor units can provide year-round heating and cooling comfort for residential, multi-family and light commercial applications. They are designed to operate with Ruud indoor units with cooling and heating capacities certified under the AHRI Certification program.

- Attractive, louvered wrap around jacket protects coil from weather extremes and yard hazards. Top grille is steel reinforced for extra strength. Cabinet is powder painted for all weather protection.
- Four sided outdoor coil design allows compressor operation with access panel removed.
- Air is discharged upward away from bushes and shrubs. The discharge pattern of the top grille provides minimum air restriction, resulting in quiet fan operation.
- Combination Grille/Motor Mount secures the fan motor to the underside of the discharge grille. The grille protects the motor windings and bearings from rain and snow.
- All controls are accessible by removing one service panel. Removable top grille provides access to the outdoor fan motor and outdoor coil.
- Compressor compartment offers additional protection from the elements and reduces operating noise.
- Single speed, 8-pole fan motor is designed for low speed, quieter, energy-saving operation.
- Non-cycling reversing valve and demand defrost.
- All models meet or exceed a 1000-hour salt spray test per ASTM B117 Standard Practice for Operating Salt Spray Testing Apparatus.

UPNL- 13 SEER SERIES

- Seven Models
- Nominal Sizes 1¹/₂ [5.28 kW] to 5 [17.6 kW] Tons

R-410A

GENERAL TERMS OF LIMITED WARRANTY

Ruud will furnish a replacement for any part of this product which fails in normal use and service within the applicable period stated, in accordance with the terms of the limited warranty.



CompressorTen (10) Years
Conditional Parts* (Registration Required)Ten (10) Years

*See Warranty Card for Details.

U	P	N	L	—	018	J	A	Z
RUUD	REMOTE HEAT PUMP	N = 13 SEER	DESIGN SERIES		COOLING CAPACITY	ELECTRICAL DESIGNATION	VARIATIONS	COOLING CONNECTION FITTING
			L = R-410A		018 = 18,000 BTU/HR [5.28 kW] 024 = 24,000 BTU/HR [7.03 kW] 030, 031 = 30,000 BTU/HR [8.79 kW] 036, 037 = 36,000 BTU/HR [10.55 kW] 042, 043 = 42,000 BTU/HR [12.31 kW] 048, 049 = 48,000 BTU/HR [14.07 kW] 060 = 60,000 BTU/HR [17.58 kW]	J = 208/230V-1-60 C = 208/230V-3-60 (UPNL 3, 3 ¹ / ₂ , 4 & 5 TON MODELS ONLY) D = 460V-3-60 (UPNL 3, 3 ¹ / ₂ , 4 & 5 TON MODELS ONLY) Y = 575V-3-60 (UPNL 4 & 5 TON MODELS ONLY)	A-SERIES = FULL FEATURED	Z = SWEAT W/SCROLL

Price

Starting at:
\$



"Proper sizing and installation of equipment is critical to achieve optimal performance. Split system air conditioners and heat pumps must be matched with appropriate coil components to meet ENERGY STAR criteria. Ask your Contractor for details or visit www.energystar.gov."