Table Top Water Heaters



Table top water heaters are a good choice when installations are in kitchens or other work areas that require additional counter space

Table Top Features

- Baked enamel counter top is acid and heat resistant
- Four inch high backsplash protects interior wall from spills and stains
- Recessed base provides comfortable standing area while working
- Channel at rear accommodates piping and permits water heater to fit snugly against back wall
- More hot water at a low operating cost

Efficiency

- .88 EF
- Well insulated for reduced standby heat loss

Performance

- FHR: 45-gallons
- Recovery rate: 21 gallons GPH at a 90 degree rise

Capacity & Dimensions

 40 Gallon model: 24 inch diameter: 25 inch depth and 36 inches high

Easy Installation & Service

 Table top surface is easily removed for access to cold and hot water outlets at top of tank, electrical connections and anode rod replacement

Longer Life

 Patented magnesium anode rod with resistor protects the tank from rust

Plus...

- Durable direct immersion resistored heating element
- Full-flow, brass drain valve
- Temperature and pressure relief valve
- Standard replacement parts

Warranty

 6-Year limited tank and parts warranty*

*See Residential Warranty Certificate for complete information

Units meet or exceed ANSI requirements and have been tested according to D.O.E. procedures. Units meet or exceed the energy efficiency requirements of NAECA, ASHRAE standard 90, ICC Code and all state energy efficiency performance criteria.




Table Top Water Heater


Large Counter Surface 40-Gallon Capacity 240 Volt AC/Single Phase Electric











DESCRIPTION		FEATURES		ROUGHING IN DIMENSIONS (SHOWN IN INCHES)					ENERGY INFORMATION	
GAL. CAP.	MODEL NUMBER	FIRST HOUR RATING G.P.H.	RECOVERY IN G.P.H. @ 90° RISE	HEIGHT A	HEIGHT TO WATER CONN. B	WIDTH C	DEPTH D	APPROX. SHIP WT. (LBS.)	ENERGY FACTOR	AVERAGE ANNUAL OPER. COST
40	PET40-2	45	21	36	33	24	25	156	0.88	\$531

- Heaters furnished with standard 240 volt AC, single phase non-simultaneous wiring, and 4500 watt upper and lower heating elements.
- If heating elements of different wattages than those shown are demanded by zone requirements, they must be specifically requested.
- Special Wiring Options A limited number of special wiring options are available. Consult factory for price and availability.

Energy Factor and Average Annual Operating Costs based on D.O.E. (Department of Energy) test procedures. D.O.E. national average fuel rate electricity 10.65¢/KWH.

In keeping with its policy of continuous progress and product improvement, Ruud reserves the right to make changes without notice.