



PUMP DATA	
FACTORY	
MODEL :	_____
H.P. :	_____
AMPS. :	_____

**NOTES:**

- \* **USE GROUND CLIP PROVIDED. FAILURE TO PROVIDE PROPER GROUND MAY RESULT IN LOCK-OUT**
- \*\* **PUMP USED MUST BE RATED 9.8 AMPS MAX OR 1/2 HP MAX. PUMP DELAY ADJUSTABLE BETWEEN 3 AND 10 MINUTES.**
- REPLACE WIRING WITH 105°C WIRE ONLY AND 150°C AS NOTED.**

APPROVED BY:
CHECKED BY:
ORIG E.O. 3311
12/13/00
CHG E.O. 4277
07/24/08
<i>Raupak</i>

WIRING DIAGRAM IID ECONOMASTER FIRING MODE – ON/OFF	
INPUTS:	334,000/399,000 BTUH
SIZE:	<b>330/400</b>
TYPE:	<b>WH</b>

KEY	
—	LOW VOLTAGE
---	FIELD INSTALL
—	LINE VOLTAGE
---	FIELD INSTALL
BK	BLACK
BL	BLUE
BR	BROWN
GY	GRAY
G	GREEN
R	RED
O	ORANGE
V	VIOLET
W	WHITE
Y	YELLOW
<b>152518</b>	<b>1</b>