



COMMERCIAL PRODUCT PORTFOLIO



Raypak[®]
A Rheem[®] Company

BOILERS, WATER HEATERS & POOL HEATERS

MID EFFICIENCY



MVB®

500 MBTUH - 4 MMBTUH

H 84-86.2% Efficiency¹

WH 85-87% Efficiency²

P 83-83.3% Efficiency³

Cascades up to 8 units.

¹Cat. I vent 84%. Cat. IV vent 85%-86.2%.

²Cat. I vent 83-83.3%. Cat. IV vent 85%-87%.

³Pool sizes vary by model.



Hi Delta®

300 MBTUH - 2.3 MMBTUH

H 84% Efficiency

WH 83.1-85% Efficiency

P 83.1% Efficiency³

FlexGas® option for dual fuel (H, WH only, excludes model 2002).

Cascades up to 8 units.

SureRack® vertical racking option.



Delta Limited®

400 MBTUH - 2.3 MMBTUH

H 84% Efficiency

WH 83.1-85% Efficiency



Delta® SS

100 MBTUH - 399 MBTUH

H 84-85% Efficiency

WH 85% Efficiency

ATMOSPHERIC



Raytherm®

511 MBTUH - 4 MMBTUH

H 82% Efficiency

WH 82% Efficiency

TANKS



Stainless Steel Indirect Heater

30 - 115 Gallons

444 stainless steel construction

444 stainless steel coil heat exchanger



Stainless Steel Storage Tank

110 Gallons

444 stainless steel construction

Indoor or outdoor installation



DHW Tanks – Stock and Custom

80 - 1794 Gallons

ASME and Non-ASME

Vertical and horizontal



ASME Hydronic Buffer Tanks

40 - 139 Gallons

Vertical and horizontal

BOILERS, WATER HEATERS & POOL HEATERS

HIGH EFFICIENCY



XVers® + KÖR™

1 MMBTUH - 4 MMBTUH

H 94.5-95.7% Efficiency
Stainless steel fire-tube.
Cascades up to 8 units.



XTherm®

1 MMBTUH - 4 MMBTUH

H 96% Efficiency
WH 97% Efficiency
P 97% Efficiency

Hybrid: copper or cupronickel finned water-tube with secondary stainless steel condensing water-tube.
Cascades up to 8 units.



XVers®

855 MBTUH - 3 MMBTUH

H 95.5-96.2% Efficiency
Stainless steel fire-tube.
Cascades up to 8 units.
HO₂T™ (O₂ Trim system) optional.



XFIIRE™ optional

300 MBTUH - 1 MMBTUH

H 96-96.5% Efficiency
WH 96-96.5% Efficiency
Stainless steel water-tube.
Cascades up to 8 units.



XVers L™

399 MBTUH - 850 MBTUH

H 97.2-98% Efficiency
Stainless steel fire-tube.
Cascades up to 8 units.



Triton®

130 MBTUH - 400 MBTUH

WH 95-98% Efficiency
80 gallon, 100 gallon. ASME and Non-ASME.
SU - Base models; SS - Premium models.
LeakSense™, LeakGuard™ (SS models only),
Built in BACnet port (SS models only), and
Advanced Power Anode Protection.



XPak FT®

85 MBTUH - 399 MBTUH

H 94.8-96% Efficiency
Stainless steel fire-tube.
Wall mounted.
Cascades up to 8 units.

POOL & SPA HEATERS

PROFESSIONAL SERIES



Professional

266 MBTUH - 399 MBTUH

P 82% Efficiency

Featuring ProTek Shield™, Gas



Professional Heat Pump

140 MBTUH - 170 MBTUH

P 6.1 ~ 5.8 C.O.P. (80,80,80)⁴

133 MBTUH - 155 MBTUH

P 5.8 ~ 5.3 C.O.P. (80,63,80)⁴



Professional X94

399 MBTUH

P 94% Efficiency, Gas



Professional Indirect

1 MMBTUH - 2 MMBTUH

P 96% Efficiency

Cascades up to 8 units.

ASME POOL & SPA



ASME Digital

199 MBTUH - 399 MBTUH

P 82% Efficiency

Featuring ProTek Shield™, also available as Low NO_x, Gas

ACCESSORIES



Indirect Heat Exchangers

45 MBTUH - 495 MBTUH

Stainless Steel or Titanium

H Hydronic **WH** Water Heating **P** Pool/Spa

 Raymote Equipped  EcoNet Equipped

 Gas  Electric

⁴Tested to AHRI 1160. All Models comply with Florida 4.0 minimum C.O.P. requirements.